

november | 23



Photo
Designed by Deborah Doherty

Tech Editor, Dawn Catanzaro

FINISHED MEASUREMENTS

40½ (43½, 48½, 51½, 55½) [58½, 62½, 65½, 68½]"

103 (110.5, 123, 131, 141) [148.5, 159, 166.5, 174] cm

Shown in size 1 with +8" of ease.

SIZES

1 (2, 3, 4, 5) [6, 7, 8, 9]

YARN

10 (10, 11, 12, 13) [14, 15, 16, 17] skeins Woolfolk Luft (109 yards / 100 meters / 50 grams)

Optional: 5 yards of matching colored worsted or sport weight yarn for seaming

Sample colors in photographs: L24

NEEDLES AND NOTIONS

Needle A (gauge needle): US 9 (5.5 mm), or size needed to obtain gauge, 24 or 32" circular needles and set of dpns

Needle B (transition needle): US 7 (4.5 mm), or two sizes smaller than gauge needle, 24" circular needle

Needle C (for ribbing): US 6 (4 mm), or three sizes smaller than gauge needle, 24 or 32" circular needles and set of dpns

Cable needle, tapestry needle, markers, locking markers, waste yarn, holders

GAUGE

20 sts and 24 rows for 4"/10 cm with Needle A (gauge needle) in Braid cable and Stockinette stitch pattern, blocked

22 stitches and 32 rows 4"/10 cm with Needle C in Rib Stitch, blocked

NOTES

The hems of *november* / 23 are worked separately, then joined in the round. The Braid cable pattern is worked over 9 stitches from a chart.

Sleeves are worked in the round from the cuff to the sleeve cap using either dpns or the Magic Loop Method. It may be necessary to adjust needle size to maintain the same gauge while working in the round on a smaller circumference. Shoulders are seamed and sleeves set in place. Use a sport or worsted weight yarn in a matching color to sew seams. The collar is picked and worked flat, overlapping and sewn in place at the base.

STITCHES AND TECHNIQUES

Rib Stitch (worked flat)

RS row: *k2, p2; repeat from * to last 2 stitches, k2.

WS row: *p2, k2; repeat from * to last 2 stitches, p2.

Rib Stitch (in the round)

All rounds: *k2, p2; repeat from * to the end.

Slip Stitch Edge (collar only)

RS row: slip the first stitch knitwise {s1} with yarn in back, pattern to the end.

WS row: slip the first stitch purlwise {s1} with yarn in front, pattern to the end.

3/3/3 Braid Cables

3/3 RC: sl 3 to cn and hold to back, k3, k3 from cn, k3.

3/3 LC: k3, sl 3 to cn and hold to front, k3, k3 from cn.


Sloped bind off

Step 1: Work the first bind off row as usual.

Step 2: One row before the next bind off, work to the last stitch of the row, slip last stitch pwise.

Step 3: Begin the next bind off by slipping 2 sts kwise, one at a time, then pass the first slipped st over the second to bind off 1 st. Bind off the remaining stitches as usual.

CHART



LEGEND

□ Knit

● Purl

 3/3 LC (left cross): Slip 3 sts onto CN and hold in front, knit 3 sts from the left needle, knit the stitches from the CN.

 3/3 RC (right cross): Slip 3 sts onto CN and hold in back, knit 3 sts from the left needle, knit the stitches from the CN.

DIRECTIONS

HEM

Make 2.

Note: to decrease, use p2tog over 2 purl stitches.

Using Needle C, cast on 118 (126, 138, 146, 158) [166, 178, 186, 194] stitches as follows: *2 Long Tail cast on, 2 Long Tail Purl cast on; repeat from * to last 2 stitches, 2 Long Tail cast on. Do not join. Work in Rib Stitch pattern with Slipped Stitch edges as established for 3¼." Break the yarn leaving a 6" tail and set aside on a holder or waste yarn. Make the 2nd hem. Change to Needle B.

Decrease Row, RS: *work in pattern decreasing 17 (19, 21, 23, 27) [29, 33, 35, 37] stitches evenly; pm, place the hem from the holder back on the LH needle and repeat from * once, placing BOR as the last marker. Join without twisting and begin working in the round. 202 (214, 234, 246, 262) [274, 290, 302, 314] stitches.

Note: place locking markers connecting the two pieces at each side split to prevent twisting until sides are secure.

Knit 1 round.

BODY

Change to Needle A.

Set up Round: *k11 (14, 19, 22, 26) [29, 33, 36, 39], (p1, k9, p1, k6) 5 times, k5 (8, 13, 16, 20) [23, 27, 30, 33]; slip side marker and repeat from * once more to BOR.

Cable design

Use the 3/3/3 cable braid chart.

*k11 (14, 19, 22, 26) [29, 33, 36, 39], (cable chart, k6) 5 times, k5 (8, 13, 16, 20) [23, 27, 30, 33], sm; repeat from * one time to BOR.

Work in pattern as established, until the piece measures 14½ (14½, 14½, 15, 15) [15, 15½, 15½, 15½]" from the cast on edge, ending on an odd chart round, 2 (2, 3, 3, 4) [4, 5, 5, 6] stitches before the BOR.

Divide for Front and Back

Bind off the next 4 (4, 6, 6, 8) [8, 10, 10, 12] stitches, work in pattern to 2 (2, 3, 3, 4) [4, 5, 5, 6] stitches before the side marker, place these 97 (103, 111, 117, 123) [129, 135, 141, 145] stitches on a holder or waste yarn. Bind off the next 4 (4, 6, 6, 8) [8, 10, 10, 12] stitches, work in pattern to the end. Begin working the Back flat. 97 (103, 111, 117, 123) [129, 135, 141, 145] stitches.

BACK

Work 1 WS row.

Shape Armholes

Decrease row, RS: k1, k2tog, work in pattern to the last 3 stitches, ssk, k1.

Repeat the Decrease row every RS row 4 (7, 9, 12, 13) [16, 17, 18, 18] more times; then every 4th row 1 time.

85 (85, 89, 89, 93) [93, 97, 101, 105] stitches.

Work in pattern until armhole measures 6½ (7, 7½, 8¼, 9) [9½, 10¼, 11, 11¼]" (total 40 (42, 46, 50, 54) [58, 62, 66, 70] rows)

Shape Neck and Shoulders

Use the Sloped Bind Off method for best results (see Techniques).

Work in pattern for 33 (33, 35, 35, 37) [37, 39, 41, 43] stitches, place these stitches on waste yarn or holder. Bind off the next 19 stitches, work in pattern to the end. Work 1 WS row. Bind off 3 stitches at the neck on the next 4 RS rows. 21 (21, 23, 23, 25) [25, 27, 29, 31] stitches.

Left Shoulder

Next WS row: bind off 6 (6, 7, 7, 7) [7, 8, 9, 9] stitches at the shoulder 2 (2, 2, 2, 1) [1, 2, 2, 1] times, then 0 (0, 0, 0, 8) [8, 0, 0, 10] stitches 0 (0, 0, 0, 1) [1, 0, 0, 1] time, and *at the same time* on the RS rows, bind off 1 stitch at the neck 2 times. Bind off the remaining 7 (7, 7, 7, 8) [8, 9, 9, 10] stitches on the last WS row.

Right Shoulder

Place stitches back on the needle and attach yarn at the neck with WS facing. Bind off 3 stitches at the neck on the next 4 WS rows. Next RS row: bind off 6 (6, 7, 7, 7) [7, 8, 9, 9] stitches at the shoulder 2 (2, 2, 2, 1) [1, 2, 2, 1] times, then 0 (0, 0, 0, 8) [8, 0, 0, 10] stitches 0 (0, 0, 0, 1) [1, 0, 0, 1] time, and *at the same time* on the WS rows, bind off 1 stitch at the neck 2 times. Bind off the remaining 7 (7, 7, 7, 8) [8, 9, 9, 10] stitches on the last RS row.

FRONT

Place front stitches back on the needle, attach yarn with WS facing. 97 (103, 111, 117, 123) [129, 135, 141, 145] stitches. Work 1 WS row.

Shape Armholes

Decrease row, RS: k1, k2tog, work in pattern to the last 3 stitches, ssk, k1. Repeat the Decrease row every RS row 1 more time. 93 (99, 107, 113, 119) [125, 131, 137, 141] stitches. Work 1 WS row.

Shape Neck and Armholes

Next row, RS: k1, k2tog, work in pattern for 39 (42, 46, 49, 52) [55, 58, 61, 63] stitches, place these stitches on waste yarn or holder. Bind off 9 stitches, work in pattern to the last 3 stitches, ssk, k1. 41 (44, 48, 51, 54) [57, 60, 63, 65] stitches. Work 1 WS row.

Right Front

Note: do *not* use Sloped Bind off for the following 2 decrease rows. Next 2 RS rows: bind off 1 stitch at the neck, work in pattern to the last 3 stitches, ssk, k1. 4 stitches decreased. 37 (40, 44, 47, 50) [53, 56, 59, 61] stitches. Work 1 WS row.

Neck Shaping edge, RS: K5, k2tog, work in pattern

Armhole Decrease edge: work in pattern to the last 3 stitches, ssk, k1.

Work the Neck Shaping edge every RS row, 14 (14, 13, 11, 10) [8, 5, 3, 0] times, then every 4th row 3 (3, 4, 6, 7) [9, 12, 14, 16] times, then every 6th row 0 (0, 0, 0, 0) [0, 0, 0, 1] time. *At the same time*, work Armhole Decrease edge every RS row 0 (3, 5, 8, 9) [12, 13, 14, 14] times, then every 4th row 1 time, then when the armhole measures 8 (8½, 9, 9¾, 10½) [11, 11¾, 12½, 13¾]" begin Shoulder Shaping.

Shoulder Shaping, WS: bind off 6 (6, 7, 7, 7) [7, 8, 9, 9] stitches at the shoulder 2 (2, 2, 2, 1) [1, 2, 2, 1] times, then 0 (0, 0, 0, 8) [8, 0, 0, 10] stitches 0 (0, 0, 0, 1) [1, 0, 0, 1] time. Bind off the remaining 7 (7, 7, 7, 8) [8, 9, 9, 10] stitches on the last WS row.

Shape Left Neck

Attach yarn on the WS at the neck.

Next 2 WS rows: Bind off 1 stitch at the neck, work in pattern to the end. 1 stitch decreased.

Note: do *not* use Sloped Bind off for these 2 stitches.

At the same time, on the next 2 RS rows: k1, k2tog, work in pattern to the end. 1 stitch decreased.

Armhole Decrease edge: work in pattern to the last 3 stitches, ssk, k1.

Neck Shaping edge, RS: work in pattern to last 7 stitches, ssk, K5.

Work Armhole Decrease edge every RS row 0 (3, 5, 8, 9) [12, 13, 14, 14] times, then every 4th row 1 time, then when the armhole measures 8 (8½, 9, 9¾, 10½) [11, 11¾, 12½, 13¼]" begin Shoulder Shaping. *At the same time*, work the Neck Shaping edge every RS row, 14 (14, 13, 11, 10) [8, 5, 3, 0] times, then every 4th row 3 (3, 4, 6, 7) [9, 12, 14, 16]times, then every 6th row 0 (0, 0, 0, 0) [0, 0, 0, 1] time.

Shoulder shaping, RS: bind off 6 (6, 7, 7, 7) [7, 8, 9, 9] stitches at the shoulder 2 (2, 2, 2, 1) [1, 2, 2, 1] times, then 0 (0, 0, 0, 8) [8, 0, 0, 10] stitches 0 (0, 0, 0, 1) [1, 0, 0, 1] time. Bind off the remaining 7 (7, 7, 7, 8 (8, 9, 9, 10) stitches on the last RS row.

SLEEVES

Make 2.

Note: to decrease, use p2tog over 2 purl stitches.

Using Needle C, cast on 56 (56, 56, 60, 60) [60, 64, 64, 64] stitches as follows: *2 Long Tail cast on, 2 Long Tail Purl cast on; repeat from * to the end, place marker. Join without twisting. Work in the Rib Stitch pattern for 3¼." Change to Needle B.

Decrease Round: work in pattern decreasing 5 (5, 5, 7, 7) [7, 7, 7, 7] stitches evenly. 51 (51, 51, 53, 53) [53, 57, 57, 57] stitches. Knit 1 round. Change to Needle A.

Cable design

Use the 3/3/3 cable braid chart.

K3 (3, 3, 4, 4) [4, 6, 6, 6], pm, (cable chart, k6) 2 times, cable chart 1 time, pm, k3 (3, 3, 4, 4) [4, 6, 6, 6].

Work the Cable pattern as established for 6 rounds.

Next round, Sleeve Increase round: k2, RLI, knit to marker, sm, work in pattern to next marker, sm, knit to the last 2 stitches, LLI, k2.

Repeat the Sleeve Increase round every 7 (6, 6, 6, 5) [5, 5, 4, 4]th round, 12 (13, 14, 14, 15) [17, 17, 19, 22] more times. 77 (79, 81, 83, 85) [89, 93, 97, 103] stitches.

Work in pattern as established, until piece measures 19 (19, 19, 19½, 19½) [19½, 20, 20, 20]" from the cast on edge, ending on an odd chart round, 2 (2, 3, 3, 4) [4, 5, 5, 6] stitches before the BOR.

Bind off the next 4 (4, 6, 6, 8) [8, 10, 10, 12] stitches, work in pattern to the end. Turn and work flat, working 1 WS row in pattern as established. 73 (75, 75, 77, 77) [81, 83, 87, 91] stitches.

Double Decrease row, RS: k2, DDR, work in pattern to last 6 stitches, DDL, k2. 4 stitches decreased.

Repeat Double Decrease row every 4th row 0 (0, 0, 1, 2) [3, 5, 6, 7] more times, then every RS row, 5 (5, 5, 4, 3) [3, 1, 1, 1] times. 49 (51, 51, 53) [53, 53, 55, 55, 55] stitches.

Work 1 WS row.

Bind off 3 stitches on the next 2 rows. 43 (45, 45, 47, 47) [47, 49, 49, 49] stitches.

Bind off all stitches on the next RS row.

FINISHING

Use the hem tails and make 2 over stitches at the connection points to secure them. Weave in ends. Block to schematics. Using mattress stitch or another invisible method, sew shoulder seams. Sew sleeves into armholes.

COLLAR

Note: the collar is worked flat with Slipped Stitch edges.

With RS facing and Needle C, pick up 45 (47, 51, 55, 61) [63, 67, 71, 75] stitches on the Front Right neck edge, 52 stitches across the back, and 45 (47, 51, 55, 61) [63, 67, 71, 75] stitches on the Front Left neck edge. 142 (146, 154, 162, 174) [178, 186, 194, 202] stitches.

Set up row, WS: pfb, p1, kfb, pfb, k2, Rib Stitch (WS) to last 4 stitches, pfb, kfb, p1, pfb. 6 stitches increased.

Row 1, RS : sl1, Rib Stitch to last 3 stitches, k3.
Row 2, WS: sl1, Rib Stitch to last 3 stitches, p3.

Work Rows 1 and 2, 7 more times or until the collar measures 2", ending with a WS row. Bind off in pattern from the RS.

With RS facing, using mattress stitch or other invisible, sew the Front Right Slipped Stitch edge to the raw edge of the Front neck. With WS facing, sew the Front Left Slipped Stitch edge to that seam.

Weave in ends. Steam block collar and seams or wet block the entire garment again.

ABBREVIATIONS

BOR	beginning of round
DDL	double decrease, left leaning: slip 2 sts to a cable needle (CN), hold to front, lining sts up with the next 2 sts on the LH needle. [K first st on CN and first st on LH needle tog] twice.
DDR	double decrease, right leaning: slip 2 sts to a cable needle (CN), hold to back, lining sts up with the next 2 sts on the LH needle. [K first st on the LH needle and first st on CN tog] twice.
dpn	double pointed needle
k	knit
kwise	as if to knit
k2tog	knit 2 sts together
LLI	lift the left leg of the stitch 2 rows below the first stitch on the right hand needle, knit into it. 1 stitch increased
m	marker
p	purl
pm	place marker
pwise	as if to purl
RLI	lift the right leg of the stitch below the first stitch on the left hand needle, knit into it. 1 stitch increased
RS	right side
sl	slip
sm	slip marker
ssk	slip slip knit (slip 2 sts kwise, one at a time onto the right hand needle, place back on left-hand needle, knit together through the back loop)
WS	wrong side
wyib	with yarn in back
wyif	with yarn in front

november | 23 schematic

